

CAT. NO.	DESCRIPTION OF ITEM	PRICES (PER UNIT) IN RUPEES
----------	---------------------	--------------------------------

with a 15 amp. Power point. Dynamically and statistically balanced blowers with air velocity 0.5 m/s make the unit least vibrant with minimum noise level i.e. less than 65db. Clean air velocity 90 +/- 20 FPM at the outlet of Hepa filters.

Standard Size (Working Area)	2' x 2'	3' x 2'	4' x 2'
Wooden Body	35000/-	38000/-	56000/-
MS Body	38500/-	58000/-	77000/-
SS Body	49000/-	74000/-	98000/-

STAR-51	TISSUE CULTURE HOOD	42000/-
---------	---------------------	---------

Made of sunmica clad thick wooden board and stainless steel working top the unit has frame at front fitted with transparent plexi glass and has an arrangement for keeping the door open if desired. Fitted with one U.V. Germicidal light and 1 florescent light. Provided with S.S. Top.
Out Side Size: 1200 x 600 x 600mm

OPTIONAL

A) EXHAUST SYSTEM AT COST EXTRA	6850/-
---------------------------------	--------

STAR-52	AIR CURTAIN
---------	-------------

An air Curtain is a modern device which, when installed on a door, forms an invisible curtain of continuous air and thus prevents escape of conditioned air and entry of outside hot, humid, dirty and unwanted polluted air. The cabinets of Air Curtain are made of cold rolled Mild Steel sheets. The blowers are made of high quality aluminum sheets, duly balanced both, statically as well as dynamically on computerized digital balancing machines, designed to provide uniform air with minimum noise and no vibration. All units are thoroughly tested at works and meet the highest standards. The motors used are of continuous rating with sealed ball-bearings.

Size Door width	
600 mm	11000/-
900 mm	13500/-
1200 mm	16000/-
1500 mm	20000/-
1800 mm	24000/-

OPTIONAL : Door Operated Switch	8500/-
---------------------------------	--------

STAR-53	INNOCULATION CHAMBER
---------	----------------------

Made of sunmica clad thick wooden board and plywood at back. The side windows are provided with thick plexi glass and front side is fitted with slanting glass door. Inside sunmica clad. Lower portion is provided with glove ports and gauntlets on front window. One fluorescent tube and one ultra violet tube are fitted inside the chamber.

Outside Size: 27" x 20" x 16"	30500/-
Outside Size: 40" x 24" x 22"	37300/-

STAR-54	TUBE ROTOR FOR 36 TUBES	11900/-
---------	-------------------------	---------

Design for rotating test tube / culture tubes. having 10" dia. Suit able for 36 tubes of 16 / 30 tubes of 25 mm dia. The disc can be set at any angle. Suitable to works on 220V 50 AC only. With cord and plug complete with all accessories. Provided with 1 tube carrier.

Additional Rotating tube carrier	2300/-
Timer	3200/-

STAR-55	V.D.R.L. ROTATOR	9800/-
---------	------------------	--------

It is useful for VDRL test, serological and other tests requiring gentle rotation. With imported timer with variable speed from 70-210 RPM. The rotator has covered metal platform 13"x13" with spring holder clamp indicator lamp and on/off switch. Works on 220/230 volts AC.



STAR-52



STAR-148



STAR-53



STAR-55