

CAT. NO. DESCRIPTION OF ITEM PRICES (PER UNIT) IN RUPEES

OPTIONAL:			
(a) Chiller up to 5 deg C			47000/-
(b)do -20 deg C			74000/-
(c) Voltage Stabilizer for Chiller			6000/-
(d) Digital RPM indicator			5000/-
(e) Vacuum Pump (Single Stage)	1 ltr	3 ltr	5ltr
. ,	14900/-	17900/-	28500/-

STAR-85 ROTARY VACUUM EVAPORATOR PREMIUM

Vertical unit to concentrate & analyze the samples with the facilities of speed variation. Heating at constant temperature through digitally controlled water bath vertical freezing. Motor speed 10-120 rpm motorized up & down temperature range 0-100 deg C with digital display. Motorized lift for up & down movement with the option of manual

capacity: 1 ltr	9850 0/-
capacity: 3 ltr	18800 0/-
Capacity: 5 ltr	238000/-

OPTIONAL:			
(a) Chiller up to 5 deg C			4700 0/-
(b)do -20 deg C			7400 0/-
(c) Voltage Stabilizer for Chille	r		600 0/-
(d) Digital RPM indicator			500 0/-
(e) Vacuum Pump (Single Stag	ge) 1 ltr	3 ltr	5ltr
	14900/-	17900/-	2850 0/-



STAR-86

STAR-86 ROTARY VACUUM PUMP

Vacuum pumps are mounted on a heavy steel base plate and have a wide range of sealed pumps. Fitted with heavy duty electric motor, all pumps are V-Belt driven at a speed of 400 RPM. Pumps are fabricated out of high grade cast iron and are worked on sophisticated machines to give accuracy in microns, thus leading to very high sustained vacuum. Supplied in single stage or double stage models. As a safety device all "ICON" vacuum pumps are fitted with belt guard as a standard feature. To work on 220/230 volts A.C. supply.

N. Company			Chamber Size	
	Motor Cap.	Single Stage	Double Stage	
25 ltr/min	0.25 H.P.	12000/-	1650 0/-	
50 ltr/min	0.25 H.P.	14000/-	2200 0/-	
75 ltr/min	0.25 H.P.	16000/-	2490 0/-	
100 ltr/min	0.50 H.P.	19000/-	2750 0/-	
150 ltr/min	0.50 H.P.	21000/-	2850 0/-	
2 00 ltr/min	1.00 H.P.	25000/-	3250 0/-	
3 00 ltr/min	1.50 H.P.	30000/-	4100 0/-	



STAR-87

Following Accessories may be Supplied on extra cost (a) Vacuum Gauge 1200/ (b) Non Return Valve 2500/ (c) Moisture Trap 2500/ (d) Oil (P/Ltr.) 300/

STAR-87 VACUUM-CUM-PRESSURE PUMP (MONOBLOCK BELTLESS) with oil With suitable motor (a) Capacity 45 ltrs. Fitted with ¼ H.P. Motor 11500/(b) Capacity 75 ltrs. Fitted with ½ H.P. Motor 16000/-



STAR-88

STAR-88 VACUUM-CUM-PRESSURE PUMP (DIAPHARGM TYPE)

With suitable motor, it is also double stage pump and creates the vacuum through a diaphragm

(a) Capacity 25 ltrs. Fitted with ¼ H.P. Motor	11000/-
(b) Capacity 45 ltrs. Fitted with ½ H.P. Motor	18000/-
(c) Canacity 75 ltrs. Fitted with ½ H.P. Motor	22000/-