

CAT. NO. DESCRIPTION OF ITEM PRICES (PER UNIT) IN RUPEES

SIZE	Ltr	Price
300 x 250 x 100 mm (6 holes of 75 mm dia)	8 ltrs	6500/-
300 x 350 x 100 mm (9 holes of 75 mm dia)	12 ltrs	7500/-
350 x 400 x 100 mm (12 holes of 75 mm dia)	15 ltrs	8500/-
OPTIONAL ACCESSORIES:		
1) Stirrer with Motor and speed regulator		4000/-

STAR-12 WATER BATH CYLINDRICAL

Single walled, electrically operated, Made of thick Stainless Steel with concentric rings. Temp. range from ambient to 100 deg C with an accuracy of +/- 1 deg C and is controlled by thermostat

200 x 150 mm (Dia x Depth)		350 0/-
250 x 250 mm (Dia x Depth)		450 0/-

STAR-13 WATER BATH CYLINDRICAL (DOUBLE WALLED)

2) Digital Temperature indicator cum controller (with an accuracy of +-0.5 deg C.

Double walled with inner made of stainless steel, outer of heavy mild steel duly powder coated. Insulation is made with thick glass wool. Fitted with concentric rings, thermostat controlled. Temperature can be maintained up to 100 deg C

Available in following sizes:

200 x 150 mm	590 0/-
250 x 250 mm	690 0/-

OPTIONAL ACCESSORIES

Digital Temperature indicator cum controller (with an accuracy of +- 1 deg C.) 6000/-

STAR-14 SEROLOGICAL WATER BATH

These units are double walled with inner chamber made up of S.S. sheet and outside of M.S. duly powder coated. The gap between the walls is filled with special grade glass wool in order to avoid thermal losses A drain plug is also fitted to the unit. The inner chamber fitted with tubular type heating element is covered with perforated removable S.S. tray. Temperature from ambient to 100 deg C is controlled by "IMPORTED THERMOSTAT" hydraulic capillary type thermostat with an accuracy of +-1 deg C. Supplied complete with 220/230 volts A.C. supply. Single phase 50 Hz.

Size (Dia X Depth)			
300 x 250 x 175 mm	for 2 racks		600 0/-
300 x 300 x 175 mm	for 4 racks		790 0/-
455 x 300 x 175 mm	for 6 racks		990 0/-
455 x 455 x 175 mm	for 8 racks		1290 0/-
OPTIONAL ACCES	<u>Innovation</u>	S to Pro	tect

OPTIONAL ACCESSORIES

a) STIRRER with 1.20 HP Motor and speed regulator	4000/-
b) Digital Temperature indicator cum controller	6000/-

STAR-15 WATER BATH (FULLY AUTOMATIC)

Double walled, inner & outer chamber made of Stainless Steel, Lid is also made of S. Steel, The inner & outer chamber is insulated with glass wool to prevent any heat loss. Temp. is maintained from ambient to 100 deg C and digitally controlled by digital temp. indicator cum controller with an accuracy of 0.5 deg C. Heating is done by heating elements with in-built water circulator. Fitted with a automatic low level water cut off device to auto cut the heater. It is have a special feature of detachable panel with all the arrangement like heaters, circulator, low high cutoff device, fuse etc. are in the panel itself.

10"x 10"x 7" (WxLxD)	32900/-
12" x 10" x 7" (W x L x D)	35300/-
15" x 12" x 7" (W x L x D)	38300/-



6000/-

STAR-11



STAR-13



STAR-14